

MASTERS SERIES

ARABELLA


STRAIGHTENED FLOW PATTERN (SFP)

VERTICAL OR HORIZONTAL




HORSEPOWER	1	2	3 & 3½	5	7½	10
HT x DIA ft UPPER	5.5 x 7	7 x 10	8.5 x 12	13 x 18	Consult Factory	
HT x DIA ft LOWER	2 x 24	4 x 35	4 x 38	5 x 55	Consult Factory	
ELECTRICAL RATING Ph VOLTAGE AMPS	1 120 19	1 208-240 12.6	1 (3½HP) 208-240 15.2	1 208-240 27.1	Consult Factory	
	3 208-240 9.6	3 208-240 6.3	3 (3HP) 208-240 10.1	3 208-240 18		
	3 208-240 5.4	3 440-480 3.1	3 (3HP) 440-480 5.1	3 440-480 9		
HT x DIA m UPPER	1.8 x 2.4	2.4 x 3.6	3.5 x 4.9	4 x 5.5	Consult Factory	
HT x DIA m LOWER	0.9 x 7.9	1.1 x 8.2	1.4 x 11.6	1.5 x 16.8	Consult Factory	
ELECTRICAL RATING Ph VOLTAGE AMPS	1 220-230 8	1 208-230 10.5	1 220-230 19	1 208-230 24	Consult Factory	
	3 380-415 2.6	3 380-415 3.7	3 380-415 5	3 380-415 8		


MASTERS SERIES® DESIGN TYPES



**1 - 5 HP Masters Series
 Vertical Design**
 (Min. Operating Depth - 3ft.)



**1 - 5 HP Masters Series
 Horizontal Design**
 (Min. Operating Depth - 16in.)





**7.5 - 10 HP Masters Series
 Cart Design**
 (Min. Operating Depth - 4ft.)

- 1 -** Interchangeable nozzles
- 2 -** Low profile float design with recessed pockets for LED & RGBW Lighting
- 3 -** Stainless steel intake screen
- 4 -** Patented, high-efficiency molded composite impeller system
- 5 -** Exclusive custom-designed oil-cooled energy efficient motors with stainless steel motor housing and top plate
- 6 -** AquaLock Connector (ALC) electrical quick disconnect
- 7 -** Exclusive underwater cable disconnect
- 8 -** Individual high density polyethylene floats are in-water adjustable
- 9 -** Rugged stainless steel compact cart design
- 10 -** Adjustable Night Glow LED or RGBW Lighting
- 11 -** Oversized floatation type tires for ease of launching

MASTERS SERIES

INSTALLATION



CONTROL PANEL



CONTROL PANEL COMPONENTS

- Outdoor rated, lockable enclosure constructed of galvanized steel powder coated gray
- Standard enclosure size 16" x 16" x 6" for 1-5HP and 24" x 20" x 6" for 7.5-10HP (1Ph) 30" x 24" x 8" for 7.5-10HP (3Ph)
- Overcurrent protection
- Ground fault protection
- Motor contactor and overload
- Capacitors (single phase only)
- Digital timers with battery backup
- LED lighting circuit included in all control panels
- Custom Control Panels for multiple units and options available

