

MASTERS SERIES

COLONIAL


STRAIGHTENED FLOW PATTERN (SFP)

VERTICAL OR HORIZONTAL




HORSEPOWER	1	2	3 & 3½	5
HT ft UPPER	17	19	20	30
HT x DIA ft LOWER	8 x 22	10 x 26	12 x 35	22 x 60
ELECTRICAL RATING Ph VOLTAGE AMPS	1 120 19	1 208-240 12.6	1 (3½HP) 208-240 15.2	1 208-240 27.1
	1 208-240 9.6	3 208-240 6.3	3 (3HP) 208-240 10.1	3 208-240 18
	3 208-240 5.4	3 440-480 3.1	3 (3HP) 440-480 5.1	3 440-480 9
	3 440-480 2.7			
HT m UPPER	4.3	4.4	5	9.1
HT x DIA m LOWER	2.7 x 7.3	3 x 7.6	3.3 x 6.4	6.7 x 18.7
ELECTRICAL RATING Ph VOLTAGE AMPS	1 220-230 8	1 208-230 10.5	1 220-230 19	1 208-230 24
	3 380-415 2.6	3 380-415 3.7	3 380-415 5	3 380-415 8

MASTERS SERIES® DESIGN TYPES



1 - 5 HP Masters Series Vertical Design
 (Min. Operating Depth - 3ft.)



1 - 5 HP Masters Series Horizontal Design
 (Min. Operating Depth - 16in.)

- 1 - Interchangeable nozzles
- 2 - Low profile float design with recessed pockets for LED & RGBW Lighting
- 3 - Stainless steel intake screen
- 4 - Patented, high-efficiency molded composite impeller system

- 5 - Exclusive custom-designed oil-cooled energy efficient motors with stainless steel motor housing and top plate
- 6 - AquaLock Connector (ALC) electrical quick disconnect
- 7 - Exclusive underwater cable disconnect

